

Attack DP Technical Specifications

Attack Model:	DP 35 Profi	DP 45 Profi	DP 75 Profi
	14-35 kW	18-45 kW	30-75 kW
Nominal heat output:	48-120 kBtu	61-154 kBtu	102-255 kBtu
Efficiency:	86%	86%	86%
Max. operation overpressure:	45 PSI	45 PSI	45 PSI
Water Capacity:	21 Gallons	28 Gallons	32 Gallons
Combustion chamber volume:	38.3 Gallons	48.9 Gallons	92.5 Gallons
Electrical input:	70 W	70 W	70 W
Min.temperature of return water at operation:	65 °C	65 °C	65 °C
Flue gas temperature:	260 °C	260 °C	260 °C
Weight:	860 lbs.	926 lbs.	1,433 lbs.
Noise level:	65 dB	65 dB	65 dB
Specified chimney draught:	23 Pa	23 Pa	23 Pa
C.H. water connection:	1 1/2"	2"	2"
Flue connection:	6"	6"	6"
A --Height:	43.3"	43.3"	53.1"
B --Width:	23.6"	23.6"	29.5"
C --Depth:	49.2"	53.1"	63"

Eco Heat Sales

Phone: 315-386-2878

Fax: 315-386-3009

www. Ecoheatonline.com

Email: info@ecoheatonline.com